

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

BRAYT T11 POLISHING COMPOUND



PRODUCT DESCRIPTION

Brayt T11 polishing compound contains high quality polishing minerals which guarantees quick elimination of defects and high gloss. Because of optimized bonding does not burn in during polishing while being easy to clean. It's universal product suitable for each type of gelcoat, PU and PE lacquers in automotive, furniture industry and composite materials.

PHYSICAL AND CHEMICAL PROPERTIES

Capacity:	150g; 1kg; 3 kg
Density:	1,23 g/cm ³
Cut level:	9/10
Gloss level:	6/10
Color:	white

USAGE

- Apply compound on the surface or applicator (foam or lambswool).
- Spread compound on the surface by machine with minimum RPM.
- Slowly increase the speed to max. 1800 RPM and polish surface with medium pressure.
- Polish surfaces until the scratches have been removed gradually reducing the speed and pressure.

STORAGE

Product works best when its temperature is 15 – 25°C.

Storage in sealed container at 0 – 45°C.

WARRANTY PERIOD

24 months from production date.

All information are based upon the precise laboratory studies and many years of experience. The good market position does not release us from the constant supervision of our products quality. However we are not responsible for the final effects of the improper storage or application of our products, as well as for work inconsistent with the good craft practice.

TROTON Sp. z o.o.
Ząbrowo, Poland

TROTON Sp. z o.o

Address: Ząbrowo 14A, 78-120 Gościno, Poland, Tel: +48 94 35 123 94
Tel/Fax: +48 94 35 126 22 Website: www.troton.com.pl Email: troton@troton.com.pl



January 2018

TROTON Sp. z o.o

Address: Ząbrowo 14A, 78-120 Gościno, Poland, **Tel:** +48 94 35 123 94
Tel/Fax: +48 94 35 126 22 **Website:** www.troton.com.pl **Email:** troton@troton.com.pl